

Teagle

EKR Flail Mower



Medium Duty - ideal for use on smaller tractors for cutting grass and clearing light undergrowth up to 2 - 3 cm diameter.

Hammer Flails for long life and a clean finish. The combination of high speed and an angled cutting edge lifts the undergrowth to give a clean neat finish.

Front or Rear Mounting by simply unbolting and refitting the linkage

540 or 1000 RPM PTO Speeds are selected simply by interchanging the gearbox and rotor pulleys.

Skids & Full Width 139 mm Roller give good height control with minimal risk of scalping.

All Bearings are internal and greasable for long life



Specifications	115	125	135	145	160
Width Across Side Plates(m)	1.15	1.25	1.35	1.45	1.60
Overall Width (m)	1.28	1.37	1.47	1.57	1.72
Height (cm)	73	73	73	73	73
Length (cm)	78	78	78	78	78
No. of Hammers	10	12	12	14	14
Weight (kg)	280	295	320	350	370
Number of Drive Belts	2	3	3	3	3
PTO Speed	540/1000 RPM (By Interchanging Pulleys)				
Power Req. (HP)	18 - 22	22 - 25	25 - 30	30 - 35	35 - 40



Manufactured in Italy by Berti

The Company's policy is one of continuous improvement and development, therefore specifications are subject to change without notice.

Teagle Machinery Ltd.,
Blackwater, Truro
Cornwall TR4 8HQ

Tel: 01872 560592
e-mail: sales@teagle.co.uk
website: www.teagle.co.uk